

# SPL400

## FUME EXTRACTOR FOR SMALL AM SYSTEMS



LIGHT DUTY



QUIET OPERATION

**DISCOVER  
OUR CUSTOM  
CONFIGURATIONS**




1.877.978.2876 • [quatroair.com](http://quatroair.com)


Left to right: SPL400 Laser Fume Extractor and SPL400 with capture arm

- Ideal for AM applications generating low debris
- Medium pressure motorized brushless impeller
- Enhanced mobility with heavy duty lockable casters
- Multi-stage filtration system: pre-filter, HEPA and chemical filter
- Whisper quiet operation
- Optional digital control panel

### FILTERS



F164  
Pleated Pre-filter



F075  
Medical Grade HEPA



F072-GPC  
Chemical Filter

STANDARD CONFIGURATION

Air Flow:	510 m <sup>3</sup> /h / 300 CFM
Motor(s):	Motorized impellers, backward inclined, non-overloading
Voltage:	120V or 230V
Dimensions:	13"W x 16"D x 20"H / 330mm x 406mm x 508mm
Filter Sequence:	4" high capacity pleated pre-filter, 30% ASHRAE (F164) 6" Medical grade HEPA Filter 99.97% (F075) 2" Chemical filter (F072-GPC)
Optional Inlets:	3" or 4" diameter
Discharge:	Recirculation grille
Sound Level:	54 dBA at full speed
Remote Control:	Optional
Suction hose:	6 feet (2m) of heavy duty hose & clamps